



ENERGY POWER. The air cooled multifunctional units of EnergyPower line are able to provide cooling, heating and domestic hot water at the same time and with the same unit. Those multifunctional units, with capacity up to 1130 kW, are dedicated to 4-Pipe systems and are ideal for buildings with simultaneous need of ambient heating, cooling and domestic hot water, such as hotels and multifunctional buildings. The range includes models with both Scroll or Inverter Screw compressors. Units are available with **R410A**, **R452B**, **R454B**, **R134a** and **R513A** refrigerants.





MAXI POWER. The MaxiPower air cooled, water cooled and condensersless liquid Chillers and Heat Pumps with Screw compressors cover capacities up to 2350 kW. Dedicated models feature Inverter technology on compressors, pumps and fans for an higher efficiency even at part load. The range is available in different variants and with different energy efficiency levels. The MaxiPower range includes models with **HFO-R1234ze** refrigerant (GWP<1) and models with **R134a** and **R513A** refrigerants.





TURBOLINE. The TurboLine range, equipped with Turbocor Magnetic Levitation compressors, reaches an extremely high efficiency with the highest EER and SEER / SEPR in the market and a low starting current, in addition to maximum reliability and an extra silent operation. The range includes air cooled and water cooled models with a wide capacity range up to 3900 kW. The Turboline range includes models with **HFO-R1234ze** refrigerant (GWP<1) and models with **R134a** and **R513A** refrigerants.



REMOTE CONDENSERS AND HYDRONIC MODULES

The chiller ranges completed by a whole range of Remote Condensers, with EC Inverter fans and different sound levels, and Remote Hydronic Modules up to 2500 litres.



PACKAGED ROOF TOP UNITS



AIR X. The Packaged Roof Top units of AirX series are characterised by single or double panelling, EC Inverter Plug-Fans and Scroll Inverter compressors. The units are available in different configurations with the addition of a Mixing Box and can be supplied with a Wheel Heat Recovery section. Units are available with **R410A** refrigerant.





AIR PLUS. The Packaged Roof Top units of AirPlus series feature single skin, EC Inverter Plug-Fans and Scroll compressors. The units are available in different configurations with the addition of Mixing Box, Free-Cooling section and Thermodynamic Coil-Boost Heat Recovery. Units are available with **R410A** refrigerant.





AIR MAXI. The Packaged Roof Top units of AirMaxi series feature double skin and EC Inverter Plug-Fans, also with Inverter Scroll compressors. The units are available in different configurations with the addition of a Mixing Box, a Free-Cooling section and a Cross-Flow, Wheel or Thermodynamic Coil-Boost Heat Recovery. Units are available with **R410A** refrigerant.



CONDENSING UNITS

A comprehensive range of Condensing units from 9 to 190 kW with different technical solutions and noise levels is available to complete the CLINT product range. Units are available for **R410A** refrigerant.



FAN COIL UNITS

FAN COIL UNITS WITH CABINET AND FOR BUILT-IN INSTALLATION. Fan Coil units for floor, ceiling or built-in installation, with several air flow configurations and capacity up to 7,3 kW, available both with 3-Speed or EC Inverter fans. Also available is a line of fan coil units with cabinet and built-in models with a depth of 130 mm and EC Inverter tangential fans from 1.1 to 4.1 kW.



WALL MOUNTED, WATER CASSETTE AND DUCTABLE FAN COIL UNITS. Wall Mounted units up to 5,4 kW, Water Cassette up to 11 kW and Ductable Fan Coil units up to 43 kW, available with 3-Speed or EC Inverter fans.



G.I. INDUSTRIAL HOLDING SPA
Via G. Agnelli, 7 • 33053 LATISANA • ITALY
Tel. +39 0432 823011 • Fax +39 0432 773855
www.clint.it • e-mail: info@clint.it

A Company of:



Sales Offices:

Europe and North & South Africa:

G.I. INDUSTRIAL HOLDING SpA
Via G. Ambrosio, 4
33053 LATISANA • ITALY
Tel. +39 0431 1967011 • Fax +39 0431 1967060
www.gind.it • e-mail: info@gind.it

Middle-East and Central Africa:

G.I. Middle East Fze Dmcc
Jumeirah Lakes Towers • Cluster W
Unit No. 801 • Tiffany Towers
P.O. Box 449869, DUBAI • U.A.E.
Tel. +971 4 569 0062
www.gime.ae • e-mail: info@gime.ae

Asia-Pacific:

G.I. INDUSTRIAL ASIA HOLDING Sdn Bhd
D-12-05, Menara Mitraland,
No 13A, Jalan PJU 5/1, Kota Damansara PJU5,
47810 PETALING JAYA, Selangor • MALAYSIA
Tel. +60 3 7890 0829 • Fax +60 3 7890 0829
www.gindasia.com.my • e-mail: info@gindasia.com.my

Production Plants:

G.I. INDUSTRIAL HOLDING SpA
Via G. Ambrosio, 4
33053 LATISANA • ITALY

G.I. INDUSTRIAL HOLDING SpA
Via Delle Industrie, 5
33050 RONCHIS • ITALY

G.I. INDUSTRIAL HOLDING SpA
Via Max Piccini, 11/13
33061 RIVIGNANO TEOR • ITALY

GIMEK Zrt
Rozália Park, 11
H-2051 BIATORBÁGY • HUNGARY
www.gimek.hu

02.2025

G.I. INDUSTRIAL HOLDING S.p.A. is not responsible for possible errors of this catalogue and can change, without prior notice, the present data.

VISIT www.clint.it



G.I. INDUSTRIAL HOLDING S.p.A. participates in the EEC programme for LCP-HP, FCU and AHU. Check on-going validity of certificate: www.eurovent-certification.com

02.2025



PRODUCT OVERVIEW



LIQUID CHILLERS AND HEAT PUMPS



COMPACT LINE. The CompactLine liquid Chillers and Heat Pumps range is the ideal solution for residential or small commercial areas. Compactness and low energy consumption are the key benefits of this range, available with Inverter Scroll compressor and with **R452B** and **R454B** refrigerants.



THERMICA. The air-to-water Heat Pumps of Thermica range are dedicated to room heating and domestic hot water production, supplying **high water temperature** (up to 65°C) and being able to work down to -20°C outside air. Being reversible, they are also able to supply chilled water for air conditioning during the summer period. The whole range has high efficiency both at full load and partial loads and the units, from 20 to 182 kW, work with **R454C** refrigerant with low GWP, less than 150, enabling them to respect the future requirements of the European Community.



BOOSTER. The water-to-water Heat Pumps of Booster range are the best solution for systems where **very high temperature** (up to 80°C) hot water production is required for domestic use, room heating or industrial processes. The wide operating range makes these units perfectly integrable in any system solution, including 4-pipe systems for air conditioning and industrial heat recovery. Units are available with **R134a** and **R513A** refrigerants.



ECO V-THERM. The new range of air-to-water Heat Pumps in **R290**, with heating capacities from 48 to 166 kW, is an environmentally friendly and efficient solution for room air conditioning and domestic hot water production; the units can produce water at **high temperature** (up to 70°C) and can operate down to -20°C outside air temperature. The refrigerant R290 (Propane) has a GWP = 3 and meets the future requirements of the European Community for reduced environmental impact. The Heat Pumps are available in basic or high-efficiency version, ensuring high performance both at full and part load and very low noise levels.



AQUA PLUS. The AquaPlus air cooled, water cooled and condensersless liquid Chillers and Heat Pumps range is dedicated to small and medium areas in commercial or industrial buildings, up to 180 kW. Compactness and easy installation are the key benefits of this range. AquaPlus range is available in several levels of energy efficiency, featuring Inverter technology on Scroll compressors and, as option, on fans and circulation pumps. Dedicated Heat Pumps for hot water production at **medium temperature** (up to 55°C) are also available. Units are available with **R410A**, **R452B** and **R454B** refrigerants.



POWER V-TECH. The new range offers a series of air-to-water liquid Chillers available in high and very high efficiency versions with Scroll compressors, up to three per circuit, ensuring optimal load management and high reliability. The range is available with **HFO-R1234ze** refrigerant, which significantly reduces environmental impact due to its low global warming potential (GWP<1). In addition, the POWER V-TECH range features V-shaped condensing modules with Microchannel coils (optional with copper/aluminium). With a capacity ranging from 200 to 600 kW, it is an ideal solution for applications requiring high energy efficiency and reliable performance, making it an excellent choice in terms of quality and sustainability.



MULTI POWER. The MultiPower range of liquid Chillers and Heat Pumps is based on multi-Scroll technology, for high partial load efficiency as the load is divided between the different compressors, up to 12 on a double refrigerant circuit, according to the required cooling capacity. The MultiPower range is available in different energy efficiency levels also with Inverter technology and includes a line of dedicated Heat Pumps for hot water production at **medium temperature** (up to 55°C). The family includes both air cooled and water cooled models with a capacity range up to 1220 kW. Units are available with **R410A**, **R452B** and **R454B** refrigerants.



1. AIR COOLED LIQUID CHILLERS AND HEAT PUMPS FOR RESIDENTIAL & LIGHT COMMERCIAL APPLICATION



1.1 Liquid Chillers and Heat Pumps with Scroll Inverter compressor and plate heat exchanger

UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES
CHA/IG/A 51÷81	INVERTER SCROLL	9,7-18	12-20	2. AIR COOLED LIQUID CHILLERS AND HEAT PUMPS FOR COMMERCIAL & INDUSTRIAL APPLICATION



2.1 Liquid Chillers and Heat Pumps with Scroll compressors and plate or shell and tube exchanger

UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES																																									
CHA/IK/A 91÷151	INVERTER SCROLL	26-42	29-48	 2.3 Dedicated Heat Pumps for high temperature (up to 65°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHA/F/ML/WP 102-P÷504-P</td><td></td><td>30-157</td><td>32-182</td><td> 2.2 Dedicated Heat Pumps for medium temperature (up to 55°C) hot water production with Scroll compressors and plate heat exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>CHA/K/A/WP 182-P÷604-P</td><td></td><td>48-163</td><td>56-197</td><td>  2.3 Dedicated Heat Pumps for high temperature (up to 65°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHA/F/ML/WP 102-P÷504-P</td><td></td><td>30-157</td><td>32-182</td><td> 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table> </td></tr></tbody></table>  2.5 Liquid Chillers with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th></tr></thead></table> </td></tr></tbody></table> </td></tr></tbody></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHA/F/ML/WP 102-P÷504-P		30-157	32-182	 2.2 Dedicated Heat Pumps for medium temperature (up to 55°C) hot water production with Scroll compressors and plate heat exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>CHA/K/A/WP 182-P÷604-P</td><td></td><td>48-163</td><td>56-197</td><td>  2.3 Dedicated Heat Pumps for high temperature (up to 65°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHA/F/ML/WP 102-P÷504-P</td><td></td><td>30-157</td><td>32-182</td><td> 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table> </td></tr></tbody></table>  2.5 Liquid Chillers with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th></tr></thead></table> </td></tr></tbody></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	CHA/K/A/WP 182-P÷604-P		48-163	56-197	 2.3 Dedicated Heat Pumps for high temperature (up to 65°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHA/F/ML/WP 102-P÷504-P</td><td></td><td>30-157</td><td>32-182</td><td> 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table> </td></tr></tbody></table>  2.5 Liquid Chillers with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th></tr></thead></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHA/F/ML/WP 102-P÷504-P		30-157	32-182	 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHV/P/WP 152-P÷504-P		40-130	48-164		UNITS NAME
UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES																																									
NEW CHA/F/ML/WP 102-P÷504-P		30-157	32-182	 2.2 Dedicated Heat Pumps for medium temperature (up to 55°C) hot water production with Scroll compressors and plate heat exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>CHA/K/A/WP 182-P÷604-P</td><td></td><td>48-163</td><td>56-197</td><td>  2.3 Dedicated Heat Pumps for high temperature (up to 65°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHA/F/ML/WP 102-P÷504-P</td><td></td><td>30-157</td><td>32-182</td><td> 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table> </td></tr></tbody></table>  2.5 Liquid Chillers with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th></tr></thead></table> </td></tr></tbody></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	CHA/K/A/WP 182-P÷604-P		48-163	56-197	 2.3 Dedicated Heat Pumps for high temperature (up to 65°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHA/F/ML/WP 102-P÷504-P</td><td></td><td>30-157</td><td>32-182</td><td> 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table> </td></tr></tbody></table>  2.5 Liquid Chillers with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th></tr></thead></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHA/F/ML/WP 102-P÷504-P		30-157	32-182	 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHV/P/WP 152-P÷504-P		40-130	48-164		UNITS NAME										
UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES																																									
CHA/K/A/WP 182-P÷604-P		48-163	56-197	 2.3 Dedicated Heat Pumps for high temperature (up to 65°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHA/F/ML/WP 102-P÷504-P</td><td></td><td>30-157</td><td>32-182</td><td> 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table> </td></tr></tbody></table>  2.5 Liquid Chillers with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th></tr></thead></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHA/F/ML/WP 102-P÷504-P		30-157	32-182	 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHV/P/WP 152-P÷504-P		40-130	48-164		UNITS NAME																				
UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES																																									
NEW CHA/F/ML/WP 102-P÷504-P		30-157	32-182	 2.4 Dedicated Heat Pumps for high temperature (up to 70°C) hot water production with Scroll compressors and plate exchanger <table><thead><tr><th>UNITS NAME</th><th>TECHNOLOGY</th><th>❄️ (kW)</th><th>🔥 (kW)</th><th>FEATURES</th></tr></thead><tbody><tr><td>NEW CHV/P/WP 152-P÷504-P</td><td></td><td>40-130</td><td>48-164</td><td></td></tr></tbody></table>	UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES	NEW CHV/P/WP 152-P÷504-P		40-130	48-164																																
UNITS NAME	TECHNOLOGY	❄️ (kW)	🔥 (kW)	FEATURES																																									
NEW CHV/P/WP 152-P÷504-P		40-130	48-164																																										
UNITS NAME																																													